



DOOR

Glazed on the whole surface

SEALING

Cut rubber membrane

EXTERNAL

Pre-lacquered sheet metal

Colour customization



SHELVES

Height adjustable

LOCK

Closing the system by key

INSIDE

Stainless Steel
Each column is individually adjustable for all bottle shapes ranging from 33Cl to 50cl
Horizontal loading

FIFO SYSTEM

Simple and quick access avoiding the opening door

LIGHTING

LED

THERMOSTAT

Display and adjustment of the temperature

TECHNICAL DATA «Table top»

External dimensions L x D x H (mm)	587 x 523 x 1088	Weight (Kg)	51
Net volume (liters)	77	Customizable surface area (m ²)	0,91
Capacity (PET 500 mL)	65	Temperature (°C)	2 to 8
Units / container-truck (20'/40'/13,6m)	60/120/138	Cooling gas	Hydrocarbon R-600a
Capacity per column (PET 500 ml)	11 + 2	Noise level (dB)	39

DONNÉES TECHNIQUES FIFO «XL»

External dimensions L x D x H (mm)	587 x 523 x 1962	Weight (Kg)	102
Net volume (liters)	77 + 152,5	Customizable surface area (m ²)	1,71
Capacity (PET 500 mL)	65 + 96	Temperature (°C)	2 to 8
Units / container-truck (20'/40'/13,6m)	30/60/69	Cooling gas	Hydrocarbon R-600a
2-year warranty for parts and labour		Noise level (dB)	39