



**DOOR**

Glazed on the whole surface

**SEALING**

Cut rubber membrane

**EXTERNAL**

Pre-lacquered sheet metal  
**Colour customization**



**SHELVES**

Height adjustable

**LOCK**

Closing the system by key

**INSIDE**

Stainless Steel  
Each column is individually adjustable for all bottle shapes ranging from 33Cl to 50cl  
Horizontal loading

**FIFO SYSTEM**

Simple and quick access avoiding the opening door

**LIGHTING**

LED

**THERMOSTAT**

Display and adjustment of the temperature

**TECHNICAL DATA «Table Top»**

External dimensions L x D x H (mm)	587 x 523 x 1088	Weight (Kg)	51
Net volume (liters)	77	Customizable surface area (m <sup>2</sup> )	0,91
Capacity (PET 500 mL)	65	Temperature (°C)	2 to 8
Units / container-truck (20'/40'/13,6m)	60/120/138	Cooling gas	Hydrocarbon R-600a
Capacity per column (PET 500 ml)	11 + 2	Noise level (dB)	39

**TECHNICAL DATA FIFO «XL»**

External dimensions L x D x H (mm)	587 x 523 x 1962	Weight (Kg)	102
Net volume (liters)	77 + 152,5	Customizable surface area (m <sup>2</sup> )	1,71
Capacity (PET 500 mL)	65 + 96	Temperature (°C)	2 to 8
Units / container-truck (20'/40'/13,6m)	30/60/69	Cooling gas	Hydrocarbon R-600a
		Noise level (dB)	39

2-year warranty for parts and labour

realized by NEFTIS



[www.fifogc.com](http://www.fifogc.com)

**SAS SACISO**  
TÉL. +33 (0)9 71 52 46 15  
e-mail. [contact@fifogc.fr](mailto:contact@fifogc.fr)

Follow us

